

Ingersoll Rand

Single-stage Air Compressors, Electric Drive

Legendary Performance

Ingersoll Rand, the world's leader in air compressor manufacturing, is proud to bring industrial quality to the commercial and contractor trades.

Designed for the professional, our 3-5 hp single-stage compressors are ideal for almost anyone, from individuals that thrive on do-it-yourself projects to the professional air compressor user. When performance is defined by maximum operating pressure, increased air flow and extended duty cycles, Ingersoll Rand is the product of choice. You'll get a compressor that features maximum air power, reliable precision engineered components and a durable design that is built to last!



Benefits

- High capacity compressor (up to 18.1 cfm) delivers air with the power to do the job right and in less time
- 100% continuous duty for the toughest applications
- Efficient finger valves that are easy to operate, easy to maintain
- Durable cast iron construction
- Long-lasting extended pump life — over 5,000 hours for years of trouble-free service
- High pressure operation, up to 135 psig
- Extended two-year warranty with use of Ingersoll Rand's All Season Select® synthetic lubricant

 **Ingersoll Rand**
Industrial Technologies

Standard Features

Oil-lube, Single-stage, Electric Drive

Durable design

Features 100% cast iron cylinders and frame

100% continuous duty cycle

Provides trouble-free performance in the most demanding conditions

Safe operation

Manual thermal overload protection of the motor, no starter required

Easy to use

Automatic start/stop pressure switch control with manual on/off lever

60 gallon vertical ASME receiver tank


Includes discharge mounted check valve, pressure gauge, drain valve, service valves and relief valves

Totally enclosed belt guard

Provides shield around flywheel, belt and motor for safe operation

Meets industry standards

Compliant to OSHA standards and UL/CSA/ASME



Delivered ready to use

All units are fully assembled, prewired and thoroughly tested prior to shipment

Even more features!

Quiet operation, 230-1-60 voltage and splash lubrication

Technical Performance

Model	Motor hp	Receiver Tank Size gal	Voltage	Capacity scfm @ 90 psig/135 psig	Maximum Pressure psig	Package Dimensions			Net Weight lb
						Length in	Width in	Height in	
SS3L3*	3	60 Vertical	230/1/60	11.3/10.3	135	20	23	66	300
SS5L5**	5	60 Vertical	230/1/60	18.1/15.5	135	20	30	71	310

*3 hp running, 7.9 peak hp

**5 hp running, 11.8 peak hp



Industrial Technologies

P.O. Box 1840
800-D Beaty Street
Davidson, NC 28036
(704) 655-5000
(704) 655-4039 Fax

Ingersoll Rand compressors are not designed, intended or approved for breathing air applications. Ingersoll Rand does not approve specialized equipment for breathing air applications and assumes no responsibility or liability for compressors used for breathing air service.

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request.

Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.